



## Available in 40 Gallon Model

### ▶ 6-Year Limited Tank and Parts Warranty\*

- Brass drain valve
- 36" high top features a four inch high integral back splash
- Baked enamel top is acid and heat resistant
- High efficiency screw-in type heating elements
- Temperature and pressure relief valve included
- Recessed base and channel in back panel permit water heater to fit snugly against wall
- Cold water inlet, hot water outlet, relief valve and electrical connections at top of tank for easy access and fast economical installation
- Rheemglas® tank lining resists corrosion and prolongs tank life
- Direct immersion resistored heating elements are completely immersed - all the heat goes into the water
- Extra thick fiberglass insulation
- Automatic thermostat keeps water at desired temperature
- Meets or exceeds National Appliance Energy Conservation Act (NAECA) requirements

\* See Residential Warranty Information Brochure for complete warranty information.

Energy Factor and Average Annual Operating Costs based on D.O.E. (Department of Energy) test procedures. D.O.E. national average fuel rate electricity 8.6¢/KWH.



DESCRIPTION			FEATURES		DIMENSIONS				ENERGY INFORMATION	
TYPE	GAL. CAP.	MODEL NUMBER	FIRST HOUR RATING G.P.H.	RECOVERY IN G.P.H. @ 90° RISE	WIDTH (IN.)	HEIGHT (IN)	HEIGHT TO WATER CONN.	APPROX. SHIP WT. (LBS.)	ENERGY FACTOR	AVERAGE ANNUAL OPER. COST

- Heaters furnished with standard 240 volt AC, single phase non-simultaneous wiring, and 4500 watt upper and lower heating elements.
- **If heating elements of different wattages than those shown are demanded by zone requirements, they must be specifically requested.**
- Special Wiring Options – A limited number of special wiring options are available. Consult factory for price and availability.

Recovery = wattage/2.42 x temp. rise °F.

Example:  $\frac{4500W}{2.42 \times 90^\circ} = 21 \text{ GPH}$